

WANDA

ATX80 A/T MASTER

PART NUMBER	DESCRIPTION
70-092-210	22-10-9
70-112-207	22-7-11
70-112-308	23-8-11
70-112-409	24-9-11
70-112-410	24-10-11
70-122-408	24-8-12
70-122-508	25-8-12
70-122-510	25-10-12



- Puncture resistant
- 4ply
- Equivalent to a 6ply
- Now delivered unbundled, no more fighting to separate and fit
- Contact your rep for delivery options.

PART NUMBER	DESCRIPTION
70-092-212	22-12.5-9
70-092-512	25-12-9
70-102-208	22-8-10
70-102-211	22-11-10
70-102-411	24-11-10
70-102-512	25-12-10
70-112-408	24-8-11



ATX78 A/T MASTER

WANDA ATV TYRES



Vee Rubber

VEE RUBBER TYRE and TUBE INFORMATION

SAFETY WARNING

When fitting new tyres:

- 1 Correct fitting and balancing by a trained technician is essential.
- 2 Check for wheel alignment.
- 3 New tyres require a 'Run In' procedure to enable the tread surface to provide correct performance.
- 4 When fitting tubes, use Talcum powder to prevent tube sticking.
- 5 Regularly check tyre inflation pressure.

TYRE IDENTIFICATION:

The Tyre Identification System gives information on:

- Tyre Width (Inch or mm)
- Aspect Ratio - Height / Width X 100
- Rim Diameter
- Maximum Speed Rating (Alpha)
- Tyre Load Index (Numeric)

Example: 120/90 – 18 70H

Tyre Width = 120 mm

Aspect Ratio = 90%

Rim Diameter = 18 inch

Load Index = 70 (355 kg)

Speed Rating = H (210 Km/h)

TYRE SIZING

METRIC	IMPERIAL	ALPHA
60/100	2.50	
70/100	2.75	
80/90	2.50/2.75	MH90
80/100	3.00	
90/90	2.75/3.00	MJ90
90/100	3.25	
100/90	3.25/3.50	MM90
100/100	4.00	
110/90	3.75/4.00	MN90
110/100	4.50	
120/80	3.75/4.25	MP90
120/90	4.25/4.50	MR90
130/90	5.00/5.10	MT90
140/90	5.50	MU90

SPEED RATINGS	J	L	M	P	R	S	T	H	V
Speed (Km/h)	100	120	130	150	170	180	190	210	240

LOAD INDEX

LI	kg	LI	kg	LI	kg	LI	kg
25	92	39	136	53	206	67	307
26	95	40	140	54	212	68	315
27	97.5	41	145	55	218	69	325
28	100	42	150	56	224	70	335
29	103	43	155	57	230	71	345
30	106	44	160	58	236	72	355
31	109	45	165	59	243	73	365
32	112	46	170	60	250	74	375
33	115	47	175	61	257	75	387
34	118	48	180	62	265	76	400
35	121	49	185	63	272	77	412
36	125	50	190	64	280	78	425
37	128	51	195	65	290	79	437

